

Statement of Evidence:

D242

Northeast Corner of Section 24, Township 38 North, Range 31 West, East Langola Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post in a mound at the corner location with pit 6 links south.

1914 County Road Book, page 120 contains a road survey by M. J. Cleveland, District Engineer, for State Road No. 7. Survey shows corner found and road run east from the corner with tie:
T.P. N 52 E 40 feet.

1931 County Engineer's Notebook No. 81 for survey of SAR 12 running east to west. Info dated 1938 shows same information by County Highway survey done by H. G. Elletson for CSAH 12, which shows corner being a hub in 4-way road intersection with ties:
8" Boxelder NW 51.5
12" Boxelder NE 43.8

1941 County Engineer's Notebook No. 151 contains a road survey for CAR 41 running south to north on township line. Corner is shown marked by a hub set in center of road intersection with SAR 12. Same ties as 1931 and new tie:
NE Cor Cheese Factory Found. SW 46.5'

1959 County Engineer's Notebook No. 220 contains a road survey for CSAH 12 running east from this corner. Corner is shown marked by a hub set in center of road intersection with SAR 15. Same ties as 1941 above and 1964 below.

1962 County Engineer's Notebook No. 230 contains a road survey for CSAH 15 running north from this corner on township line. Corner is shown marked by an iron in center of road intersection with SAR 12. Same ties as 1964 below.

1964 County Surveyor's Record Book 2, page 194, notes an iron at the corner with the following reference ties.
12" Spruce SW 97.2
TP NE 49.35
PP SW 48.45

1964 M.W.Carley notes show - found a 2" shaft at the corner location.

1974 M.W.Carley found a 2" staff at the corner location.

1974 County Highway reference ties to a RR spike:
FP SE 54.03
12" Spruce NE 60.45
Spruce SW 48.45

1989 Bruce Skipton, LS 17768, found a 2" iron shaft at the centerline of roads and filed a Certificate of Location (#195975).

1995 Comstock and Davis performed GPS work under contract with Benton County and Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to a 1 " iron pin:
N- 180355.968
E - 478838.447