

Statement of Evidence:

D282

Northeast Corner of Section 28, Township 38 North, Range 31 West, East Langola Township, 4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

5" Bur Oak	N 13 1/2 E	230 links
16" Bur Oak	N 30 W	624 links

1975 Carley/Lang did a survey and notes that this corner was marked by a found 3/4" I.P. at the centerline of roads with the following reference ties.

RH 12" W. Oak	NNE	81.90 (face tie)
RH 10" W. Oak	NE	82.71 (face tie)
RH RR tie Post	S	28.31

1980 David Regan, LS 12236, notes a cast iron monument at the corner location.

1992 County notes state a 3/4" pipe was found and lowered 6 inches.

2000 Sam Deleo, LS 40341, found a cast iron monument at the centerline of a east/west road and trail (north). He filed a Certificate of Location (#271522) and notes that the found cast iron monument does not match with the Benton County Highway Department 1992 Certificate. He also notes the following distances 2649.39 feet to the North 1/4 corner Sec 28 (cast iron monument) and 2626.92 feet to the East 1/4 corner Sec 28 (cast iron monument).

2004 Surveying & Engineering Professionals, Inc. found a CIM at the corner location.
County Coordinates obtained by GPS.
NAD 83 (1996 Adjustment)
N-174955.639
E-462783.870

2004 MN/DOT
County Coordinates obtained by GPS
NAD 83 (1996 Adjustment)
N-174955.235
E-462784.118