

Statement of Evidence:

D302

Northeast Corner of Section 30, Township 38 North, Range 31 West, East Langola Township, 4th Principal Meridian, Benton County, Minnesota.

- 1852 Original US General Land Office survey set a wood post in a mound with a pit 8 links south at the corner location.
- 1946 MN/DOT alignment map for TH 10 shows corner assumed at intersection of fence lines north and west being 1556.6 feet west of the centerline.
- 1991 David Regan, LS 12236, set a cast iron monument at the intersection of fence lines from the north and west. He filed a Certificate of Location (#223476).
- 2002 No resurvey information was found on this corner in the Benton County records.
- 2004 Westwood Professional Services, Inc. found a ½ " iron pipe with cap No. 12236 at the corner location.
County Coordinates obtained by GPS.
NAD 83 (1996 Adjustment)
N-174859.631
E-452119.896
- 2004 MN/DOT
County Coordinates obtained by GPS
NAD 83 (1996 Adjustment)
N-174859.613
E-452119.885
- 2008 Westwood Professional Services, Inc. found a ½" iron pipe with cap No. 12236 at the corner location. Corner fits 1991 Regan ties. Fence lines are longstanding evidence of section line locations. Location is accepted as marking the obliterated position. County Coordinates obtained by GPS coincide with 2004 MN/DOT position.