

Statement of Evidence:

H063

East Quarter Corner of Section 6, Township 37 North, Range 29 West, Gilmanton Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established corner marked with a wood post with bearing trees noted as:

15" Bur Oak	S 41 W	26 links
14" Bur Oak	S 70 E	? links

1933 County Engineer's Notebook No. 72 contains survey of County road running south to north through this corner marked by a spike in center of road with town road west. Ties same as listed in County Surveyor's Record Book 1, Page 471:

3 rd F.P.	W	44.4
2 nd F.P.	NW	44.5

Stationing gives distances of 2642.7 feet to the SE corner Section 6.

1963 County Highway ties:

2 nd F.P.	NW	66.95'
PP	East	36.9'

2009 The Benton County Surveyor's Office found a 3/4-inch open iron pipe in the north-south centerline of County Road 82 on the centerline of 110th Street NE to the west. The found iron measures 2650.44 feet to the southeast corner of Section 6, about 8 feet long of the 1933 measure, with a fence to the east at the south sixteenth fitting a split of the distance within a foot. The 1963 ties were searched for and not found. The found iron is considered the best available evidence of the corner location.

County Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N-161434.859
E-516343.861