

Statement of Evidence:

H243

East Quarter Corner of Section 24, Township 37 North, Range 29 West, Gilmanton Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded:

16" Basswood	N 17 E	4 links
14" Maple	S 4 W	20 links

1939 County Engineer's Notebook No. 131 contains survey of CAR 32 running south to north on township line. No corner is shown, but stationing gives distances to fence line east of 2679.7 feet to the SE corner and 2675.2 feet to the NE corner.

1993 David Regan, LS 12236, set a $\frac{1}{2}$ " I.M. on the centerline of a road north/south and a fence line east. He filed a Certificate of Location (#231247). Survey information gives distances of 2662.09 feet to the SE corner and 2693.38 feet to the NE corner.

2005 Danny Kron, LS , found $\frac{1}{2}$ " iron pipe that fit Regan's ties and used corner for breakdown of Section 24. Corner is accepted as marking the obliterated corner position.

2008 The County Surveyor's Office searched and found a PK nail with a Benton County disk flush with the surface at the centerline of north-south bituminous road (County Road No. 66) and on line with an east fence line. Position gives distance to the NE and SE corners as 2693.55 feet and 2662.27 feet respectively, which agrees with Regan's 1993 distances to same of 2693.38 feet and 2662.09 feet. Surveyor accepts position and updated ties.

Coordinates to PK nail by GPS
NAD 83 (1996 Adjustment)
N-145798.496
E-542407.167