

Statement of Evidence:

H323

East Quarter Corner of Section 32, Township 37 North, Range 29 West, Gilmanton Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post with bearing trees noted as:

14" Maple	S 56 W	25 links
12" Lynn	N 81 E	23 links

1949 County Highway Engineer's Notebook No. 169 contains road survey for CAR 37 running from south to north on the section line. Corner is shown marked by a hub set in the center of road with fence lines east and west. Ties:

6" Maple	SW	85.2
18" Elm	SW	126.4

Stationing gives distances of 2749.2 feet to the SE corner and 2760.5 feet to the NE corner with a delta angle of 0-20' right.

1957 County Surveyor's Record Book 1, page 523, shows the same ties as in 1941 to an iron. A distance of 2749.20 feet is given to the SE corner of Section 32.

1995 William Lunser, LS 9394, set a cast iron monument at the location of a found 1" square headed bolt with washers. He filed a Certificate of Location (#234184) and notes a distance of 2758.13 feet to the NE Cor Sec 32.

2003 Westwood Professional Services, Inc. found a CIM and obtained coordinates. We measured 2758.21 feet to the NE corner and 2753.23 feet to the SE corner of Section 32.

2008 The County Surveyor's Office searched and found a cast iron monument approximately 1 foot below the gravel surface on the centerline of the north-south road (95th Ave. N.E.) and on line with the west fence line. Position agrees with 1949 distances to the NE and SE corners (2758.21 ft. & 2753.23 ft. vs. 2760.5 ft. & 2749.2 ft, respectively). Surveyor accepts the CIM and updated ties.

County Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N- 134974.862

E- 521139.120