

**Statement of Evidence:**

**H353**

East Quarter Corner of Section 35, Township 37 North, Range 29 West, Gilmanton Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

This corner is noted on the following recorded plats

<i>PHEASANT GROVE TWO</i>	8/20/1992	Sidney Williamson
<i>STERLING RIDGE</i>	4/23/1998	Sidney Williamson
<i>STERLING RIDGE TWO</i>	7/28/1999	Sidney Williamson

1855 Original US General Land Office survey set a wood post with bearing trees noted as:

14" Blk Ash	S 46 W	15 links
6" Blk Ash	S 12 E	25 links

2002 Westwood Professional Services, Inc. found no record information on this corner in the Benton County records.

2005 Daniel Kron, LS 42621, reported finding a  $\frac{1}{2}$ " iron pipe that fit the plats done by Williamson. He measured 2600.23 feet to the SE corner.

2008 The County Surveyor's Office searched and found a  $\frac{1}{2}$ " iron pipe approximately 120± feet south and 40± feet west of the southeast corner of the westerly waste water pond, in a swamp. The position gives a distance of 2600.28 feet to the SE corner, which agrees well with the 2600.23 feet distance reported by Kron in 2005. Position also gives a distance to the Center of Sec. 35, as monumented, of 2642.24 ft. which agrees well with the above mentioned plats. The Surveyor accepts the position and set ties above the swamp on top of the waste water pond berm.

Coordinates Obtained by GPS to  $\frac{1}{2}$ " iron pipe

NAD 83 (1996 Adjustment)

N-134994.853

E-537089.584