

Statement of Evidence:

H171

North Quarter Corner of Section 17 Township 37 North, Range 29 West, Gilmanton Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established corner marked with a wood post with bearing trees noted as:

12" Sugar	S 85 E	7 links
15" Sugar	N 28 1/2 E	14 links

1987 Paul Wellen, LS 10461, found a 1/2 " iron pipe, 2 feet south of east-west centerline and in line with fence line north. He replaced the pipe with a cast iron monument and filed a Certificate of Location (Doc. No. 184285). His notes give measurements of 2668.59 feet to the NW corner and 2668.00 feet to the NE corner of Section 17.

2002 No resurvey information was found on this corner in the Benton County records.

2008 The County Surveyor's Office searched and found Wellen's 1987 cast iron monument. Position falls on the centerline of an east-west gravel road (95th St. NE), and on line with a tree line to the north. Distances to the NW and NE Corners measures 2668.70 ft. and 2668.01 ft., respectively. Corner falls 15.37 ft. north of a straight line. The Surveyor accepts the position as marking the best evidence and ties were updated.

County Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N-153558.706

E-518833.808