

Statement of Evidence:

H201

North Quarter Corner of Section 20, Township 37 North, Range 29 West, Gilmanton Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established corner marked with a wood post with bearing trees noted as:

9" Blk ?	S 21 1/2 E	20 links
12" W Birch	N 27 1/2 W	26 links'

A line tree was noted as a 28" Blk Oak West 8.80 chains.

1939 County Engineer's Notebook No. 158 contains road survey for CAR No. 20 running east to west along the section line. No corner is shown and stationing gives distance of 5295.2 feet for the north line of Section 20.

1987 Paul Wellen, LS 10461, found a 3/4 " iron pipe in center of east-west road and in line with tree line south. He replaced the iron pipe with a cast iron monument and filed a Certificate of Location (Doc. No. 184290). His notes give distances of 2639.75 feet to the NW corner and 2652.99 feet to the NE corner.

2002 No resurvey information was found on this corner in the Benton County records.

2008 The County Surveyor's Office searched and found the cast iron monument as set by Wellen in 1987. Distances to the NW and NE Cors. measure 2639.53 ft. and 2653.00 ft. which gives an overall distance of the north line of Section 20 as 5292.53 ft, which agree with 1939 measurements and Wellens measurements. The traveled centerline of a north-south gravel road (90th Ave NE) lies 20± ft. west of the corner. The intersection of roads would yield a position that falls further from a lost position. Wellen's cast iron monument position is accepted as the best evidence and ties were upated.

County Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N-148289.223

E-518706.429