

**Statement of Evidence:**

**H072**

Northeast Corner of Section 7, Township 37 North, Range 29 West, Gilmanton Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established corner marked with a wood post with bearing trees noted as:

24" Elm	N 17 W	47 links
24" Bur Oak	S 88 E	80 links

1933 County Engineer's Notebook No. 72 contains survey of County road running south to north through this corner in center of road with fence line east. Ties:

F.P. East 32.8'  
F.P. NE 39.1'

Stationing gives distances of 2656.7 feet to the East ¼ corner Section 7 and 2642.7 feet to the East ¼ corner Section 6 with a delta angle of 0-59' left.

1963 County Highway tie to spike:

F.P. East 47.3'

2009 The Benton County Surveyor's Office found a 3/4" iron pipe. The found iron measures 2650.44 feet north to a found 3/4" iron pipe at the east quarter corner of Section 6, with the split of the distance at the sixteenth fitting a fence east within one foot. The iron measures 2652.29 feet south to a found railroad spike, with a split of the distance at the sixteenth fitting fences east and west within 3 feet.

County Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N-158784.714

E-516304.754