

Statement of Evidence:

C013

East Quarter Corner of Section 1, Township 38 North, Range 30 West, Graham Township, 4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office set a wood post at this location and bearing trees were recorded:

6" Elm	S 5 E	15 links
4" Elm	N 68 E	14 links

Undated County Surveyor's Record Book 2, page 160, notes ties:

Cor FP	NW	39.1
Cor FP	SW	35.3
E-side Culv Wall	SE	19.8

1988 Bruce Skipton, LS 17768, dug with a backhoe and found nothing. He set a cast iron monument by lost method, proportional distance from the NE and SE corners. He filed a Certificate of Location (#191232). Survey information gives distances of 2659.99 feet to the SE corner and 2667.23 feet to the NE corner with an interior angle of 179-54-20.

2011 The Benton County Surveyor's Office found the CIM and 2 of the reference ties reported in 1988. The found CIM fits the lost position within 0.3 feet, however the distances reported in 1988 vary by 3 feet from the lost position. The north-south centerline of County Road 60 falls on line with the northeast and southeast corners of Section 1 and no definite occupation lines were found running east or west. The found CIM is accepted as marking the corner position. Coordinates were verified and reference ties created.

Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N-193918.300
E-510204.900