

**Statement of Evidence:**

**C043**

East Quarter Corner of Section 4, Township 38 North, Range 30 West, Graham Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

- 1852 Original US General Land Office set a wood post at this location and bearing trees were recorded:
- |            |        |           |
|------------|--------|-----------|
| 5" Blk Oak | S 13 E | 105 links |
| 4" Blk Oak | S 27 W | 235 links |
- 1908 County Surveyor's Record Book 2, page 164, M.J. Cleveland notes he set the corner lost with distances of 40.76 chains (2690.16 feet) to the NE corner Sec 4 and 40.95 chains (2702.70 feet) to the SE corner Sec 4. Ties:
- |             |           |          |
|-------------|-----------|----------|
| 12" Blk Oak | N 35-15 W | 19 links |
|-------------|-----------|----------|
- 1984 Paul Wellen, LS 10461, set a cast iron monument at the centerline of roads north/south and a tree line east/west. He filed a Certificate of Location (#173404). Measured 2678.97 feet to the SE corner.
- 2008 Westwood Professional Services, Inc. found a CIM fitting 1984 Wellen ties. Measured 2678.93 feet to the SE corner and 2709.14 feet to the NE corner of section 4. Location fits longstanding occupation along the east/west quarter lines of Section 3 and 4. CIM is accepted as marking the obliterated position for this corner.
- Coordinates Obtained by GPS  
NAD 83 (1996 Adjustment)  
N-193735.877  
E-494124.336