

Statement of Evidence:

C083

East Quarter Corner of Section 8, Township 38 North, Range 30 West, Graham Township, 4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at this location and bearing trees were recorded:
6" Blk Oak S 25 W 866 links

1923 County Engineer's Notebook No. 40 contains a survey for CAR No. 1 running south to north. Notes do not show this corner with a distance of 5358.9 feet for the east line of Section 8. Stationing shows PI in center of concrete culvert with distance of 2673.6 feet to the SE corner and 2685.3 feet to the NE corner with a delta angle of 1-22' right.

1925 County Surveyor's Record Book 2, pages 168 and 174, and Record Book A, Map No. 47, contains a survey of Sections 5 and 8 by Paul Zeese. County Engineer's Notebook 44, page 10, notes the corner is at the north edge of concrete culvert. (Notebook 41 notes iron pipe for corner.) Notes show line run from the SE corner of Section 8 with a distance of 2677.8 to the ¼ corner and a distance of 5367.2 feet to the NE corner of Section 8. (Notebook No. 41 distance is 5362.2 feet.)

1952 MN/DOT alignment map for TH 25 shows corner assumed in center of north-south road and in line with fences east-west. Corner is shown 56.3 feet west of new centerline. Stationing gives approximate distances of 2680.4 feet to the SE corner and 2684.1 feet to the NE corner.

Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N-

E-