

**Statement of Evidence:**

**C103**

East Quarter Corner of Section 10, Township 38 North, Range 30 West, Graham Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office set a wood post at this location and bearing trees were recorded.

12" Aspen	N 1 E	103 links
10" Aspen	S 55 W	50 links

1931 County Engineer's Notebook No. 81 for survey of Graham aid road running south to north. Corner is shown as a hub with fence lines running east and west. Same ties as listed in: County Surveyor's Record Book 2, page 158, notes an iron at the corner and page 176 notes a hub at the corner, with the following ties:

TP	E	29.5
TP	SE	40.5

Stationing gives distances of 2667.2 feet to the SE corner and 2658.4 feet to the NE corner with a delta angle of 0-11' right.

1963 County Engineer's Notebook No. 285 contains a road survey for CR 22 running south to north on section line. Corner is shown as an iron in center of road 3 feet north of an east-west fence line. Stationing gives distances of 2669.1 feet to the SE corner and 2660.2 feet to the NE corner with a delta angle of 0-06' right.

Ties:

PP	SW	58.9
Fen Cor	W	32.0
8" Poplar	NW	96.0

1990 David Regan, LS 12236, found a 1/2" iron pin in the centerline of a north/south road and a fence line east/west. He filed a Certificate of Location (#201751).

1991 Paul Wollen, LS 10461, found a 1/2" iron pipe and set a cast iron monument over it.

2005 Certificate of Survey by Ronald Engelmeyer, LS 13334, shows a distance of 2659.66 feet to the NE corner of Sec. 10.

Coordinates Obtained by GPS  
NAD 83 (1996 Adjustment)  
N-  
E-