

Statement of Evidence:

C113

East Quarter Corner of Section 11, Township 38 North, Range 30 West, Graham Township, 4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

7" Aspen	S 53 E	5 links
7" Bur Oak	S 22 W	13 links

1990 William Lunser, LS 9394, set a cast iron monument at the intersection of road north/south and a fence line east. He filed a Certificate of Location (#201525). He notes a distance of 2704.50 feet to both the NE Cor Sec 11 and the SE corners Sec 11.

2002 No resurvey information was found on this corner in the Benton County records.

2003 Westwood Professional Services, Inc. found CIM and measured 2704.72 feet to the Northeast corner and 2704.35 feet to the Southeast corner of Section 11. Corner was found to be 12.54 feet west of a straight line between section corners. Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N- 188441.570
E- 505049.765

2008 Westwood Professional Services, Inc. found a CIM and measured 2704.72 feet to the Northeast corner and 2704.35 feet to the Southeast corner of Section 11. Corner was found to be 12.54 feet west of a straight line between section corners. CIM was found on the centerline of 65th Ave. NE and on line with a fence line east. CIM fits 1990 Lunser ties. CIM is accepted as marking the obliterated position for this corner. County coordinates obtained by GPS coincide with 2003 position.