

Statement of Evidence:

C133

East Quarter Corner of Section 13, Township 38 North, Range 30 West, Graham Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office set a wood post at this location and bearing trees were recorded

6" Poplar	S 14 E	15 links
6" Poplar	N 86 W	4 links

A 6" W Oak line tree was noted South 15.50 chains and a 6" Poplar North 20.83 chains

2002 No resurvey information was found on this corner in the Benton County records.

2007 Westwood located an iron pipe capped 9394 which falls on a fence to the east approximately in the north-south centerline of the gravel road down 0.4 feet.

Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N-183126.028
E-510569.180

2007 The corner was excavated and no additional corner evidence was found. A 12-foot east-west by 16-foot north-south by 3-foot deep hole was dug to original soil. The found iron pipe falls online between section corners. From the found iron pipe the measurement north to a CIM is 2712 and to the south to a CIM is 2665. The half-mile distances in Benton County fluctuate with many half mile distances being longer than the original GLO Survey with no real consistency. Therefore, I accepted the iron pipe as marking the obliterated position and set a 1/2-inch by 14-inch iron pipe capped 19552.

2010 The Benton County Surveyor's Office found the iron pipe set in 2007, verified the 2007 coordinates and established reference ties.