

Statement of Evidence:

C153

East Quarter Corner of Section 15, Township 38 North, Range 30 West, Graham Township, 4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

10" Aspen	S 74 1/2 E	18 links
10" Aspen	S 28 W	21 links

1931 County Engineer's Notebook No. 81 for survey of Graham aid road running south to north. Corner is not shown, but a $\frac{1}{4}$ line fence is noted at 2615 feet north of the SE corner with the east line of the section being 5214.0 feet.

1963 County Engineer's Notebook No. 285 contains a road survey for CR 22 running south to north on section line. No corner is shown, but stationing notes a $\frac{1}{4}$ line fence east with distances of 2618.5 feet to the SE corner and 2599.4 feet to the NE corner.

1985 Ronald Engelmeyer, LS 13334, found no monument at this corner and set a cast iron monument at the centerline of a road north/south and a fence line east. Verified position by measurements to occupied sixteenth line and center of section. He filed a Certificate of Location (#173451).

2002 No old resurvey information was found on this corner in the Benton County Surveyor's records.

2003 Found CIM and measured 2617.83 feet to the SE corner and 2598.94 feet to the NE corner. Position agrees with previously assumed positions and is accepted as marking the obliterated corner position.
County Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N- 183070.705
E- 499887.151

2008 Westwood Professional Services, Inc. found a CIM fitting 1985 Engelmeyer ties. CIM is accepted as marking the obliterated position for this corner. Coordinates obtained by GPS coincide with 2003 position