

**Statement of Evidence:**

**C183**

East Quarter Corner of Section 18, Township 38 North, Range 30 West, Graham Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

3" Blk Oak	S 68 E	55 links
4" Blk Oak	S 15 W	300 links

1983 Paul Wollen, LS 10461, notes in his records a 1" solid iron pin in the centerline of a road north/south and a tree line west. He replaced the found iron with a cast iron monument and notes a distance of 2765.63 feet to the NE corner Sec. 19 and 2658.76 feet to the NE corner Sec 18.

1987 Paul Wollen files a Certificate of Location (#182948) for the information from 1983.

1992 Bruce Shepperd, LS 17003, found a cast iron monument in the centerline of roads north/south. He filed a Certificate of Location (#212980) and notes a distance of 2764.14 feet to the NE corner Sec 19 and a distance of 2658.63 feet to the NE corner Sec 18. He notes corner is 52.71 feet north and 2.07 feet west of the lost position. He accepted CIM as marking the obliterated position of the corner.  
County Coordinates on Certificate  
NAD 83 (1986 Adjustment)  
N- 183177.769  
E- 483824.647