

Statement of Evidence:

C243

East Quarter Corner of Section 24, Township 38 North, Range 30 West, Graham Township, 4th Principal Meridian, Benton County, Minnesota.

- 1849 Original US General Land Office set a wood post at this location and bearing trees were recorded
- | | | |
|-------------|--------|----------|
| 10" W Oak | S 1 W | 26 links |
| 12" Blk Ash | N 32 W | 39 links |
- A 10" Poplar tree was noted South 18.66 chains and an 6" Poplar North 20.47 chains
- 2002 No resurvey information was found on this corner in the Benton County records.
- 2007 The Benton County Surveyor's Office found a 1/2" iron pipe with unreadable cap. The found iron fits a split of the distances between section corners within a foot and is 5 feet east of a straight line between section corners. The iron pipe falls in the north-south centerline and on occupation lines east and west. Field lines at the sixteenth corners north and south both fall approximately 14 feet south of the sixteenth distance splits. The iron pipe is accepted as marking the obliterated corner position.
- Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N-177769.911
E-510723.565
- 2010 The Benton County Surveyor's Office found the 1/2" iron pipe down 1.4 feet in gravel road, verified the 2007 coordinates and marked references as shown.