

Statement of Evidence:

C333

East Quarter Corner of Section 33, Township 38 North, Range 30 West, Graham Township, 4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

4" Aspen	S 43 E	43 links
8" Blk Oak	S 31 W	14 links

Undated County Highway notes call for a cast iron monument on the centerline of road north/south and a fence line west with the following reference ties

TP	NE	40.21
FP	W	36.65

1952 MN/DOT alignment map for TH 218 (25) shows corner assumed at center of road north-south and fence lines east-west. Gives distance of 2717.7 feet to the NE corner.

1977 Paul Wellen, LS 10461, set a 1/2" iron pipe at a fence line east/west and a centerline of a north/south road. He notes a distance of 2716.13 feet to the NE corner Sec 33 and a distance of 2699.95 feet to the SE corner Sec 33. He filed a Certificate of Location (#147254).

2002 Westwood Professional Services, Inc. found a broken off cast iron monument.

2008 Westwood Professional Services, Inc. found a broken off CIM ~1 foot east of the traveled centerline of 45th Ave. NE and on fence lines east and west. None of 1977 Wellen ties remain. Measured 2715.56 feet to NE corner and 2699.36 feet to SE corner of Section 33 which agree with 1977 Wellen measurements. CIM is accepted as marking the obliterated position for this corner.

County Coordinate Obtained by GPS

NAD 83 (1996 Adjustment)

N-167060.096

E-495048.726