

**Statement of Evidence:**

**C343**

East Quarter Corner of Section 34, Township 38 North, Range 30 West, Graham Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1852 Original US General land Office survey established corner with a wood post set at this location and bearing trees were recorded.

12" Aspen                    N 50 1/2 W                    504 links

Undated                    County notes call for the following reference ties to a cast iron monument:

FP	NW	45.97
TP	NE	113.08
Ash	NE	131.87

1938 County Engineer's Notebook No. 122 contains a road survey for CAR 24 running north to south. Notes show no corner, but stationing notes center of cartway east on 1/4 line measuring 2662.0 feet to the NE corner and 2713.4 feet to the SE corner. (A PI is located 431.8 feet south of the cartway, indicating that the 1/4 corner would not be in the center of the road.)

1952 MN/DOT alignment map for TH 25 shows corner assumed in center of north-south road and in line with cart way east. Gives distance of 2665.5 feet to the NE corner of Section 34.

1977 Paul Wollen, LS 10461, set a 1/2" pipe at the centerline of County Road 59 (running north and south) and a cart way east. He notes a distance of 2662.27 feet to the NE corner Sec 34 and a distance of 2715.27 feet to the SE corner Sec 34.

2008 Westwood Professional Services, Inc. found a CIM in the centerline of County Road 59 and ~5 feet north of the centerline of a cartway east. Field crew notes they found a fence post leaning badly NW ~46 feet and a boxelder NE 131.9 feet which may correspond with undated county ties. Measured 2715.11 feet to the southeast corner of Section 34 which also corresponds with 1938 and 1977 measurements. CIM is accepted as marking the obliterated position for this corner.

Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N-167121.260

E-500448.721