

Statement of Evidence:

C021

North Quarter Corner of Section 2, Township 38 North, Range 30 West, Graham Township, 4th Principal Meridian, Benton County, Minnesota.

- 1849 Original US General Land Office set a wood post at this location and bearing trees were recorded
8" Bur Oak N 73 E 260 links
- 1908 County Surveyor's Record Book 2, page 162, shows corner was used by M.J. Cleveland to establish the center of Section 2. No corner information given.
- 1914 Phil Randall, Morrison County Surveyor, notes in Surveyor Record Book A, page 167, (Morrison County) a survey of Section 35-39-30. He found stake at the corner and measured 2663 feet to the SE corner and 2646 to the SW corner. Survey shows he set 1/16th corners between.
- 1988 Paul Wellen, LS 10461, searched for and found nothing. He set a cast iron monument at the centerline extension of a road from the west, and fence lines from the north and east. He notes a distance of 2639 feet from the corner set to the apparent NW corner marked by occupation. He filed a Certificate of Location (191337).
- 2008 Westwood Professional Services, Inc. found a CIM fitting 1988 Wellen ties. CIM if 0.77 feet south of proportioned distance using 1914 Randall measurements. Measured 2641.95 feet to the NW corner and 2659.28 feet to the NE corner of Section 2. CIM is accepted as marking the obliterated position for this corner. Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N-196478.328
E-502075.195