

**Statement of Evidence:**

**C071**

North Quarter Corner of Section 7, Township 38 North, Range 30 West, Graham Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at this location and bearing trees were recorded:  
10" Bur Oak                    S 33 E                    1000 links

1934 County Engineer's Notebook No. 74 contains survey for Road "O" running from east to west. Notes show no corner, but stationing gives distances to fence line north at 2660.2 feet to the NE corner and 2392.7 feet to the NW corner.

1964 County Engineer's Notebook No. 276 contains a road survey for CSAH No. 22 running west to east on section line. No corner is shown with stationing giving a distance of 5056.1 feet for the north line of Section 7.

2010 The Benton County Surveyor's Office located the east-west centerline and at a fence to the north. The east-west position fit the 1934 distances by less than a foot to the east and two feet to the west, falling 0.6 feet south of line between section corners. The long-standing occupation lines are accepted as marking the obliterated corner position. A 1/2" by 14" iron pipe capped "RLS 19552" was set to mark the obliterated corner position, GPS coordinates were obtained and reference ties established as shown.

Coordinates Obtained by GPS  
NAD 83 (1996 Adjustment)  
N-191157.569  
E-480831.755