

**Statement of Evidence:**

**C081**

North Quarter Corner of Section 8, Township 38 North, Range 30 West, Graham Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at this location and bearing trees were recorded:

10" Bur Oak	N 18 E	154 links
8" W Elm	N 25 1/2 W	211 links

1925 County Surveyor's Record Book 2, page 174, and County Engineer's Notebook 44, page 10, Paul Zeese notes he found old stake and put in iron pipe at the corner in the center of road and fence south. Notes the following distances:  
2668.4 feet to the NW Cor Sec 8 (temp corner)  
2682.6 feet to the NE Cor Sec 8

1925 County Surveyor's Record Book 2, page 168, and Record Book A, Map No. 47, contains a survey of Sections 5 and 8 by Paul Zeese. Survey notes an iron at the corner with the same distances as above.

1934 County Engineer's Notebook No. 74 contains survey for Road "O" running from east to west. Notes corner as a hub and iron in line with fences running north-south. Ties:  
FP S 31.1'  
6" Pop. NE 53.5'  
Stationing gives distances of 2681.0 feet to the NE corner and 2668.8 feet to the NW corner.

1952 MN/DOT alignment map for TH 25 shows corner in road with I.P. 33 feet south and 2680.9 feet west of the NE corner of Section 8.

1962 County Surveyor's Record Book 2, page 174, notes the following reference ties to an iron:  
6" Poplar NE 88.7  
Fen Cor S 30.7  
Fen Cor N 32.6

1964 County Engineer's Notebook No. 276 contains a road survey for CSAH No. 22 running west to east on section line. Notes show corner marked by an iron in center of road with fence lines north and south. Same ties as above in 1962. Stationing gives distances of 2668.6 feet to the NW corner and 2681.0 feet to the NE corner with a delta angle of 0-37' right.

County Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N-  
E-