

Statement of Evidence:

C111

North Quarter Corner of Section 11, Township 38 North, Range 30 West, Graham Township, 4th Principal Meridian, Benton County, Minnesota.

- 1852 Original US General Land Office set a wood post at this location and bearing trees were recorded..
- | | | |
|-----------|------------|-----------|
| 12" Aspen | N 10 1/2 E | 150 links |
| 12" Aspen | S 89 1/2 W | 360 links |
- 1908 County Surveyor's Record Book 2, page 162, shows corner was used by M.J. Cleveland to establish the center of Section 2. No corner information given.
- 1939 County Engineer's Notebook No. 128 contains survey of CAR 22 running east to west on section line. Corner is shown as a spike set in center of road in line with fences north and south. Ties:
- | | | |
|---------|----|--------|
| Cor. FP | N | 27.95' |
| FP | NW | 47.55' |
- Stationing gives distances of 2696.7 feet to the NE corner and 2774.2 feet to the NW corner with a delta angle of 1-06' left.
- 1964 County Engineer's Notebook No. 276 contains a road survey for CSAH No. 22 running west to east on section line. Notes show corner marked by an iron in center of road with fence line south. Notes fence north being 5 feet west. Ties are the same as listed in 1974 below. Stationing gives distances of 2774.2 feet to the NW corner and 2698.0 feet to the NE corner with a delta angle of 1-07 1/2' right.
- 1974 County Surveyor's Record Book 2, page 178, notes an iron with the following reference ties:
- | | | |
|----|----|-------|
| PP | SW | 118.3 |
| PP | NW | 107.7 |
- 1990 Paul Wellen, LS 10461, found a 1" iron pipe at the centerline of County Road 22 and occupation north/south. He set a cast iron monument over the found pipe and filed a Certificate of Location (#206771). Ties check with 1974 ties.
- 2008 Westwood Professional Services, Inc. found CIM fitting 1990 Wellen ties. Measured 2693.30 feet to the NE corner and 2772.89 feet to the NW which agree well with 1939 and 1964 County Engineer records. CIM is accepted as marking the obliterated position for this corner.
- County Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N-191094.773
E-502292.733