

Statement of Evidence:

C141

North Quarter Corner of Section 14, Township 38 North, Range 30 West, Graham Township, 4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

8" Aspen	North	6 links
8" Aspen	South	8 links

1944 County Engineer's Notebook No. 164 contains a road survey for CAR 25 running east to west on section line. No corner is shown with stationing distance of 5194.2 feet for the north line of Section 14.

1985 Ronald Engelmeyer, LS 13334, set a cast iron monument at the lost location between section corners (straight line and midway), which fit an occupation line south and the centerline of a road east/west. He filed a Certificate of Location (#173450).

2003 Westwood Professional Services, Inc. found CIM and obtained coordinates.
County Coordinates Obtained by GPS:
NAD 83 (1996 Adjustment)
N- 185703.007
E- 502459.912

2003 Westwood Professional Services, Inc. found a CIM fitting 1985 Engelmeyer ties. CIM falls 0.46 feet west of lost position. Measured 2673.44 feet to the NW corner and 2674.36 feet to the NE corner of Section 14. CIM is accepted as marking the obliterated position for this corner. Coordinates obtained by GPS coincide with 2003 position.