

Statement of Evidence:

North Quarter Corner of Section 19, Township 38 North, Range 30 West, Graham Township, 4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey established this corner and set a wood and bearing trees were recorded.
12" Aspen N 43 E 559 links

1914 County Road Book, page 120 contains a road survey by M. J. Cleveland, District Engineer, for State Road No. 7. Survey shows corner found and road run east-west from the corner with tie: T.P. N 36 E 33 feet. Stationing gives distances of 2394 feet to the NW corner and 2699 feet to the NE corner of Section 20.

1931 County Engineer's Notebook No. 81 for survey of SAR 12 running east to west. Corner is shown as a spike in center of road and in line with fence south. Stationing gives distances of 2703.0 feet to the NE corner and 2402.5 feet to the NW corner. Same ties as listed in County Surveyor's Record Book 2, page 194, notes a spike in the centerline of a road with the following reference ties:
TP NE 33.4
FP NW 34.2

1959 County Engineer's Notebook No. 220 contains a road survey for CSAH 12 running west to east on section line. Corner is shown marked by a spike set in center of road with fence line south. Ties.
FP S 33.8'
FP SW 43.4
Stationing gives distances of 2403.0 feet to the NW corner and 2703.0 feet to the NE corner with a deflection angle of 0-46' right.

Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N-
E-