

Statement of Evidence:

C201

North Quarter Corner of Section 20, Township 38 North, Range 30 West, Graham Township, 4th Principal Meridian, Benton County, Minnesota.

- 1852 Original US General Land Office survey established this corner and set a wood and bearing trees were recorded.

| | | |
|----------|--------|-----------|
| 5" Aspen | S 43 W | 68 links |
| 5" Aspen | N 64 W | 107 links |

- 1914 County Road Book, page 120 contains a road survey by M. J. Cleveland, District Engineer, for State Road No. 7. Survey shows corner found and road run east-west from the corner with tie: T.P. N 60 E 56 feet. Stationing gives distances of 2673 feet to the NW corner and 2652 feet to the NE corner of Section 20.

- 1931 County Engineer's Notebook No. 81 for survey of SAR 12 running east to west. Corner is shown as a spike in center of road and in line with fences north and south. Stationing gives distances of 2655.8 feet to the NE corner and 2677.0 feet to the NW corner and noted as a POT with no delta angle. Same ties as listed in County Surveyor's Record Book 2, page 196:

| | | |
|----|----|------|
| FP | S | 24.0 |
| FP | SE | 37.9 |

- 1951 MN/DOT alignment map for TH 25 and notes show the assumed corner is at the intersection of roads east/west and a fence line north-south. A distance of 2654.0 feet is noted to the NE corner Sec 20.

- 1959 County Engineer's Notebook No. 220 contains a road survey for CSAH 12 running west to east on section line. No corner is shown, but a POT is noted on fence line north and south. Ties.

| | | |
|--------|----|-------|
| Cor FP | S | 28.4' |
| FP | NW | 76.9' |

Stationing gives distances of 2679 feet to the NW corner and 2656 feet to the NE corner.

- 1992 Bruce Shepperd, LS 17003, with MN/DNR, set a 3/4" X 24" Rebar with an aluminum cap stamped "DNR Survey Marker" at the centerline of a road east/west and a tree line north and a fence line south. He filed Certificate of Location (#212982). He notes a distance of 2655.43 feet to the NE corner Sec 20 and a distance of 2678.72 feet to the NE corner Sec 19. The corner is 1.40 feet south and 11.64 feet east of the lost position.

County Coordinates on Certificate:

NAD 83 (1986 Adjustment)

N- 180407.945

E- 486622.270