

Statement of Evidence:

North Quarter Corner of Section 22, Township 38 North, Range 30 West, Graham Township, 4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post was set at this location and bearing trees were recorded.

7" Aspen	N 36 E	13 links
8" Aspen	S 9 W	25 links

1929 County Engineer's Notebook No. 54 for survey of SAR 12 running west to east. Corner is in center of road with fence north. Ties:

10" Oak	N	54.9'
12" Oak	S	27.3'
15" Oak	S45E	87.0'

Stationing gives distances of 2712.0 feet to the NW corner and 2628.0 feet to the NE corner.

1959 County Engineer's Notebook No. 220 contains a road survey for CSAH 12 running west to east on section line. Corner is shown marked by a spike set in center of road with fence line north. Fence line south is noted 16 feet east. 1962 ties to placed iron are the same as below. Stationing gives distances of 2716.2 feet to the NW corner and 2632.1 feet to the NE corner with a deflection angle of 0-51' right.

1963 County Surveyor's Record Book 2, page 200, shows an iron at this location with the following reference ties.

T.P.	NE	59.6
6x6 Cor. F.P.	N	42.7
P.P.	SW	45.6
F.P.	SE	57.8

2001 Westwood Professional Services, Inc. found a 1/2" iron pin down 1.2 feet at the intersection of the centerline of County Road 12 (running east and west) and a tree line from the north and a fence line from the south. This appears to check with the ties from 1963. A cast iron monument was set at the location of the 1/2" iron pin and established reference ties. Accepted the pin as marking the obliterated corner position. Paul Wollen, LS 10461, filed Certificate of Location (Doc. No. 285642).

2002 Measured 2715.40 feet to the NW corner and 2632.86 feet to the NE corner.
County Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N-180406.324
E-497358.347