

Statement of Evidence:

C351

North Quarter Corner of Section 35, Township 38 North, Range 30 West, Graham Township, 4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

12" Aspen	N 7 E	6 links
10" Aspen	S 36 W	7 links

1927 County Engineer's Notebook No. 80 contains a road survey for State Road No. 218 by H. G. Elletson. Survey ran from west to east. Notes show corner in centerline with fence north. Same ties as noted in County Surveyor's Record Book 2 (1928):

FP	NW	36.7
TP	NE	22.3

Stationing gives distances of 2636.2 feet to the NW corner and 2657.3 feet to the NE corner with a delta angle of 0-30' right.

1952 MN/DOT alignment map for TH 25 shows corner assumed in center of east-west road and in line with fence north with corner being 8.1 feet south of the new centerline. Stationing gives distances of 2641.0 feet to the NW corner and 2662.7 feet to the NE corner.

2011 The Benton County Surveyor's Office found a open half inch iron pipe approximate 8 feet south the of the east-west centerline of STH 25. The half inch iron pipe fits the MnDOT position for the corner with 0.5 feet based on centerline alignment monuments and fits the 1927 resurvey distances within 5 feet. The iron falls on a fence to the south and approximately on the projection of a fence a quarter mile to the north. The found iron measures 69.26 feet to an iron capped 12236 on the south ROW line and 150.04 feet north to an iron capped 12236 on the north ROW of STH 25. Believing the half inch iron is accepted as marking the obliterated corner position. Coordinates were obtained and reference ties established as shown.

Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N-169771.140

E-503071.623