

Statement of Evidence:

C062

Northeast Corner of Section 6, Township 38 North, Range 30 West, Graham Township,
4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office set a wood post at this location and bearing
trees were recorded:
8" Blk Oak N 74 W 212 links

1889 Morrison County Surveyor's Record Book A, page 22, contains a survey of
Section 32 by H. S. Clyde, which shows this corner as found stake.

1925 County Engineer's Notebook 44, page 10, notes found oak stake with iron marks.
New BT:
7" Oak NW 12.9'
Also noted in Notebook 48 with distances of 5317.0 feet to the NE corner Sec. 5
and 5203.5 feet to the SE corner Sec. 6.

1925 County Surveyor's Record Book 2, page 168, Record Book A, Map No. 47,
contains a survey of Sections 5 and 8 by Paul Zeese. Survey notes an oak stake at
the corner location with same tie as above.

Undated Highway notes call for a stake/stone at the corner with the following
reference ties:
Fen Cor SW 25.5
Fen Cor NW 30.0
County Surveyor's Record Book 2, pages 168 and 170, notes a stone at the corner
and an oak stake.

1997 MN/DOT used this corner to set the North 1/4 corner of Section 5 with a distance
of 2653.17 feet.

Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N-
E-