

Statement of Evidence:

C082

Northeast Quarter Corner of Section 8, Township 38 North, Range 30 West, Graham Township, 4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey established this corner and set a wood post in a mound for the corner location with a pit 8 links south.

1923 County Engineer's Notebook No. 40 contains a survey for CAR No. 1 running south to north. Notes show corner with ties:

TP	NE	37.5
TP	SE	44.0

1925 County Engineer's Notebook No. 44, page 10, notes corner with line run north and west.

1925 County Surveyor's Record Book 2, pages 168 and 174, and Record Book A, Map No. 47, contains a survey of Sections 5 and 8 by Paul Zeese. Survey notes the corner with the following reference ties to an iron:

TP	NE	37.5
TP	SE	44.0

1934 County Engineer's Notebook No. 74 contains survey for Road "O" running west from this corner. Notes corner as a spike in TH running north-south. Ties:

TP	NE	45.7'
TP	SE	46.4'

1952 MN/DOT alignment map for TH 25 shows corner assumed in center of roads north-south and east-west being 13.8 feet west of new centerline. Distances of 2680.5 to the North 1/4 corner Section 8 and 2681.0 feet to the North 1/4 corner of Section 9. Ties:

PP	NW	58.9
Hub	NE	41.8

1964 County Engineer's Notebook No. 276 contains a road survey for CSAH No. 22 running west to east on section line. Notes show corner marked by a nail set in center of road. Ties:

PP	NW	69.05
Sign Pst	SW	32.2

Stationing gives distance of 15.3 feet east to the center of TH 25.

1969 County Surveyor's Record Book 2, page 174, Kotsmith notes the following reference ties:

PP	NW	69.05
Sign Pst SW	32.2	
PP	NE	45.7
PP	SE	46.4

14.36 feet west of a north/south centerline

1984 Paul Wellen, LS 10461, found a 3/4" X 24" Boat Spike at the centerline of an east/west road and 13.1 feet west of the north/south centerline. He replaced the found iron with a cast iron monument and filed a Certificate of Location (#173406).

2008 Westwood Professional Services found a CIM fitting 1984 Wellen and 1964/1969 County ties. CIM is accepted as marking the obliterated position for this corner.

County Coordinates obtained by GPS

NAD 83 (1996 Adjustment)

N- 191196.943

E- 488842.001