

Statement of Evidence:

C142

Northeast Corner of Section 14, Township 38 North, Range 30 West, Graham Township,
4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

7" Bur Oak	N 65 E	16 links
14" Aspen	S 84 W	26 links

1944 County Engineer's Notebook No. 164 contains a road survey for CAR 25 running from south to west on section lines. Corner is shown marked by a hub set for the PI. Ties:

12" Bl. Oak	NW	66.8'
10" Bl. Oak	NW	63.0'

Undated County Surveyor's Record Book 2, page 178, notes the following reference tie:

7" Bur Oak	N 37 1/4 W	140 links (92.4')
------------	------------	-------------------

1955 County Surveyor's Record Book 2, page 184, notes the following reference ties to hub:

18" W Oak	NW	91.6
PP	NE	57.7
Center SE Culv	SW	42.7
Older ties:		
12" Blk Oak	NW	66.8
10" Blk Oak	NW	63.0

1985 Ronald Engelmeyer, LS 13334, found nothing marking the corner and set a cast iron monument at the centerline of roads north/south/east/west. Verified its location with sixteen occupation lines north and south. (Note: his ties to PP and Oak appear to agree with 1955 ties) He filed a Certificate of Location (#173454).

2001 Westwood Professional Services, Inc. found a CIM with the tie to an Oak NW at 92.62 feet fitting old ties and PP to the NE fitting certificate and 1955 tie.
County Coordinates obtained by GPS to CIM
NAD 83 (1996 Adjustment)
N-185738.530
E-505134.040

2008 Westwood Professional Services, Inc. found a CIM fitting 1985 Engelmeyer ties. CIM is accepted as marking the obliterated position for this corner. Coordinates obtained by GPS coincide with 2001 position.