

**Statement of Evidence:**

**C152**

Northeast Corner of Section 15, Township 38 North, Range 30 West, Graham Township,  
4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at this location and bearing trees  
were recorded.

12" Aspen	S 52 W	70 links
12" Aspen	N 64 1/2 W	75 links

Undated County Surveyor's Record Book 2, page 176, notes the following reference tie:

12" Poplar	S 7 1/4 W	72 links
------------	-----------	----------

A granite monument is noted at the corner with the following reference ties:

PP	SW	54.2
PP	SE	96.6

1931 County Engineer's Notebook No. 81 for survey of Graham aid road running south to  
north. Corner is shown marked by a large rock with town road running east and west.  
Same ties as listed in: County Surveyor's Record Book 2, page 186, H. G. Elletson notes  
a rock with the following reference ties:

NW Cor S-wall Culvert	SE	50.8
TP	N	41.2

1944 County Engineer's Notebook No. 164 contains a road survey for CAR 25 running east to  
west on section line. Corner is shown marked by a hub set over stone in center of CAR  
24. Ties same as listed above in 1931.

1962 County Highway information shows an iron pipe over a large rock at the corner with the  
following reference ties:

PP	NW	58.0
Fen Cor	NE	41.3
TP	SE	48.7

1963 County Engineer's Notebook No. 285 contains a road survey for CR 22 running south to  
north on section line. Corner is shown as an iron in 4-way road intersection. Ties are the  
same as in 1962.

1985 Ronald Engelmeyer, LS 13334, set a cast iron monument over a found 4" iron pipe in the  
centerline of roads north/south/east/west down 3.0 feet. PP to the NW fits 1962 ties. He  
filed a Certificate of Location (#173452).

2008 Westwood Professional Services, Inc. found a cast iron monument set by Engelmeyer at  
the intersection of CR 77 and CR 59. NW tie to power pole as mentioned in 1962 ties  
still remains and agrees with CIM. CIM is accepted as marking the obliterated position  
for this corner.

County Coordinates Obtained by GPS:

NAD 83 (1996 Adjustment)

N- 185667.700

E- 499786.702