

**Statement of Evidence:**

**C162**

Northeast Quarter Corner of Section 16, Township 38 North, Range 30 West, Graham Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

13" Aspen                    N 15 1/2 E                    717 links

Undated ties:

TP	SW	39.2
Cor FP	SE	42.0

1944 County Engineer's Notebook No. 164 contains a road survey for CAR 25 running east to west on section line. Corner is shown marked by a hub set over stone in center of road with town road north and south. Ties same as listed below in 1949.

1949 County Surveyor's Record Book 2, page 188, notes the following reference ties to a hub over a stone:

S-end Culvert	SE	28.6
W-end Culvert	SW	24.9

2000 Sam Deleo, LS 40341, excavated road intersection and down 3 feet found a 8" to 10" diameter wood post laying SW'ly with 16p nails driven into top, a 4" x 5' wood post laying SE'ly, and a 12" field stone with a 1 1/2" chiseled notch. He set a cast iron monument at the location of the stone, leaving the stone 1 foot NW of the cast iron monument. Filed Certificate of Location (Doc. No. 270204).

Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N-

E-