

Statement of Evidence:

C182

Northeast Corner of Section 18, Township 38 North, Range 30 West, Graham Township,
4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

12" Bur Oak	N 9 1/2 E	383 links
12" Blk Oak	N 7 W	288 links

1925 County Surveyor's Record Book 2, page 172, and Engineer's Notebook 44, page 10, notes an iron pipe with the following reference ties:

Oak	NW	38.2
Hub	SE	33

(Also in 1926 Notebook 48)

1944 County Engineer's Notebook No. 164 contains a road survey for CAR 25 running east to west on section line. Corner is shown marked by an iron pipe in center of road with town road north and south. Ties same as listed below in 1949.
Additional later tie:

PP	SW	46.8'
----	----	-------

1949 County Surveyor's Record Book 2, page 192, Elletson notes an iron with the following reference ties:

R Oak	NW	92.3
TP	NE	56.9

1978 Carley Engineering found and used the corner for a survey in Section 7.

1983 Paul Wellen's survey notes show 1 1/2" iron pipe found with a distance of 2658.76 feet to the East 1/4 corner Section 18.

1987 Paul Wellen, LS 10461, found a 2" iron pipe at the centerline of roads north/south and east/west. He filed a Certificate of Location (#182947).

1989 David Regan, LS 12236, found a 2" iron pipe at the centerline of a road east/west and a road north/south. He filed a Certificate of Location (#195022).

Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N-
E-