

Statement of Evidence:

Northeast Corner of Section 19, Township 38 North, Range 30 West, Graham Township, 4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey established this corner and set a wood post and bearing trees were recorded.

4" Blk Oak	S 72 1/2 W	53 links
4" Blk Oak	N 29 E	113 links

1914 County Road Book, page 120 contains a road survey by M. J. Cleveland, District Engineer, for State Road No. 7. Survey shows corner found and road run east-west from the corner with tie: T.P. S 48 W 40 feet.

1931 County Engineer's Notebook No. 81 for survey of SAR 12 running east to west. Corner is shown as a spike with town road north. Ties:

Cor. F.P.	NW	43.7'
Cor. F.P.	NE	38.6'

1959 County Engineer's Notebook No. 220 contains a road survey for CSAH 12 running west to east on section line. Corner is shown marked by a spike set in center of road with town road north and south. 1963 ties are the same as below to small iron.

1963 County Surveyor's Record Book 2, page 194 notes an iron with the following reference ties:

PP	SW	85.9
PP	SE	57.9
TP	NE	53.5
16" Boxelder	SW	61.9

Older ties to spike same as shown in 1931.

1983 Paul Wellen's, LS 10461, notes show found nail at corner and measured 2765.63 feet to the East 1/4 corner of Section 18.

1987 Paul Wellen, set a cast iron monument at the centerline of a road north/south and east/west. He filed a Certificate of Location (#182949).

1992 Bruce Shepperd, LS 17003, with MN/DNR, found a cast iron monument at the centerline of roads north/south and east/west. He filed a Certificate of Location (#12984). He notes a distance of 2764.14 feet to the East 1/4 corner Sec 18 and a distance of 2678.72 feet to the North 1/4 corner Sec 20 and accepted the CIM as marking the obliterated corner position.

County Coordinates on Certificate

NAD 83 (1986 Adjustment)

N- 180416.185

E- 483943.564