

Statement of Evidence:

C232

Northeast Corner of Section 23, Township 38 North, Range 30 West, Graham Township,
4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

8" Maple	S 12 1/2 W	7 links
13" Aspen	N 9 W	15 links

1914 County Road Book, page 120, contains a road survey by M. J. Cleveland, District Engineer, for State Road No. 7. Survey shows set 1 1/4 " gas pipe in place of old post. Tie: T.P. S 43 W 39 feet

1931 County Engineer's Notebook No. 81 for survey of SAR 12 running west from this corner. Corner is shown as a 5" x 7" stone monument in center of road with same ties as in 1949.
County Engineer's notebook No. 65 contains road survey for SAR No. 12 running east from this corner. Corner is shown as a granite monument with same ties as 1949.

1944 County Engineer's Notebook No. 164 contains a road survey for CAR 25 running south to north on section line. Corner is shown marked by a hub set over rock in center of SAR 12. Ties same as listed in 1949 below.

1949 County Highway Engineer, H. G. Elletson, notes a hub over a stone with the following reference ties.

Culvert wall	NE	47.3
Culvert wall	SE	47.9

1959 County Surveyor's Record Book 2, page 202 shows an iron over a stone with the following reference ties:

P.P.	NE	52.3
P.P.	SE	79.8
NE Cor Store	SW	49.4

Same information is contained in County Engineer's Notebook No. 220 that notes iron over granite monument.

1983 David Regan, LS 12236, found a 1" solid iron pin over a wood stake and stone at the intersection of the centerlines of County Road 12 (running east and west) and County Road 41 (running north and south). He set a cast iron monument over the stone and established new reference ties. A Certificate of Location was filed (#166047).

2001 Westwood Professional Services, Inc. found a cast iron monument, that fits with the 1959 and 1983 ties, at the intersection of the centerlines of County Road 12 (running east and west) and County Road 41 (running north and south) and established coordinates prior to overlay project.
County Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N-180424.692
E-505338.363

2008 Westwood Professional Services, Inc. found a cast iron monument, that fits with the 1959 and 1983 ties, at the intersection of the centerlines of County Road 12 (running east and west) and County Road 41 (running north and south). County Coordinates Obtained by GPS coincide with 2001 position.