

**Statement of Evidence:**

**C252**

Northeast Corner of Section 25, Township 38 North, Range 30 West, Graham Township,  
4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office set a wood post at this location and bearing  
trees were recorded

10" Blk Oak	N 62 E	20 links
6" Blk Oak	N 62 W	4 links
6" Blk Oak	S 64 W	4 links
6" Poplar	S 66 E	11 links

A 6" Poplar line tree was noted South 20.40 chains and a 10" Poplar North  
21.34 chains

No Date County Surveyor's Record Book 2, page 298, shows a survey for a  
cartway in Section 30 by J. A. Stanton (He was Deputy County Surveyor  
in early 1900's). He notes corner indicated by center lines of public road  
crossing.

1972 County Surveyor's Record Book 2, page 206, notes the following reference ties to  
an iron over a mower wheel:

18" Elm	SE	136.95
8" R Oak	SW	92.15

2006 A 9-foot by 18-foot by 2.5-foot deep hole was excavated by KLD with a Benton  
County backhoe on November 16. A 2.7-foot diameter steel mower wheel was  
found and a 1/2" iron pipe capped RLS 40341 was placed over the found corner  
evidence on November 29.

Coordinates Obtained by GPS  
NAD 83 (1996 Adjustment)  
N-175076.056  
E-510814.006

2010 The Benton County Surveyor's Office found a 1/2" iron pipe with unreadable cap  
down 1.2 feet in a gravel road. The 2007 coordinates were verified and reference  
ties established as shown.