

Statement of Evidence:

C292

Northeast Corner of Section 29, Township 38 North, Range 30 West, Graham Township,
4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

6" Aspen	N 78 W	34 links
8" Aspen	N 79 E	36 links

1923 County Engineer's Notebook No. 40 contains a survey for CAR No. 1 running south to north. Notes corner with ties:

TP	NW	39.0'
Cor. FP	NE	37.2'

County Surveyor's Record Book 2, page 214, notes the same ties.

Undated County Highway notes show the following reference ties:

TP	NW	40.4
Cor FP	NE	37.2
Rock	SW	45.3

1952 MN/DOT alignment map (Roll F-02) for TH 218 (25) notes a 4" square stone that is 4" thick at the corner with the following reference ties

Cor FP	SE	49.3
Cor FP	NE	39.55

The corner is at the centerline of a road east/west. Corner is 18.1 feet west of new C/L of TH 25 and a distance of 2631.0 feet to the assumed North ¼ corner Sec 29 and a distance of 2655.0 feet to the assumed North ¼ Corner Sec 28 is shown.

1990 Survey by Paul Wollen, LS 10461, shows a County monument in place 18.1 feet west of centerline of TH 25.

2002 Westwood Professional Services, Inc. located monuments around Section 21. At this corner we found a cast iron monument +/-17.5 feet west of a PK found at the intersection of the centerlines. Who or when the CIM was set is unknown.

County Coordinates Obtained by GPS (CIM)

NAD 83 (1996 Adjustment)

N-175112.701

E-489481.997

For Information – Not Corner

County Coordinates Obtained by GPS (PK at centerline)

NAD 83 (1996 Adjustment)

N-175112.700

E-489499.521