

**Statement of Evidence:**

**F083**

East Quarter Corner of Section 8, Township 37 North, Range 31 West, Watab Township,  
4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1850 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

12" Bur Oak	N 73 E	3 links
8" Bur Oak	S 63 W	29 links

This corner is noted on the following recorded plat:

*FERRY POINT ADDITION 4/17/1962 Milner W. Carley*

1961 M.W.Carley, LS 855, found a stone at the corner and shows stone 1119.9 feet east of the SE corner of Lot 35, Block 1, FERRY POINT ADDITION.

1972 Certificate of Survey filed as Doc. No. 132159, by M. W. Carley, LS 855, shows corner.

1972 M.W.Carley found a stone monument, +/-1.0 feet north of fence line and on easterly extension of FERRY POINT ADDITION.

1987 William Lunser, LS 9394, searched corner area and could not find the stone monument. Local resident stated that corner area had been graded and that stone could have been destroyed. He set a cast iron monument 1119.90 feet east of the SE corner of Lot 35 on the extension of the south line of Lot 35. Corner is 1.5 feet north of an east/west fence line. He filed a Certificate of Location (#191253).

2001 Westwood Professional Services, Inc. found a cast iron monument at the corner location.

2004 MN/DOT  
County Coordinates obtained by GPS  
NAD 83 (1996 Adjustment)  
N-156134.655  
E-457502.693

2008 Westwood Professional Services, Inc. found a cast iron monument at the corner position. Measured 1119.89 feet to the SE corner of Lot 35, FERRY POINTY ADDITION and fit ties to 1987 Lunser certificate. CIM is accepted as marking the obliterated position for this corner. Coordinates obtained by GPS coincide with 2004 MN/DOT position.