

Statement of Evidence:

F133

East Quarter Corner of Section 13, Township 37 North, Range 31 West, Watab Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

4" Blk. Oak	S 29 E	84 links
2" Blk. Oak	S 71 W	262 links

1898 County Road Book, page 163, shows road surveyed by Felix Parrent, County Surveyor, south to north on town line. Survey gives distance of 80.58 chains (5318.28 feet) along the east line with no mention of the ¼ corner.

1940 County Engineer's Notebook No. 133 contains a road survey for CAR No. 41 running south to north. No corner is shown. Stationing gives distance of 5318.3 feet for the east line of the section with a fence line east at 2721.0 feet north of the SE corner.

1979 Paul Wellen, LS 10461, found an iron pipe in the centerline of County Road 57 opposite a fence line to the east. He set a cast iron monument and filed a Certificate of Location (#154384). His notes show a distance of 2596.62 feet to NE corner and 2717.02 feet to the SE corner of Section 13.

1990 Paul Wellen found a RR spike in the centerline of County Road 57 at the location where the 1979 cast iron monument was set. (The cast iron monument is now gone). A new cast iron monument was set and a Certificate of Location (#201471) was filed.

2008 Westwood Professional Services found a cast iron monument. CIM fits 1990 Wellen ties. CIM is accepted as marking the obliterated position for this corner.
Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N- 150922.968
E- 478757.256