

**Statement of Evidence:**

**F143**

East Quarter Corner of Section 14, Township 37 North, Range 31 West, Watab Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1850 Original US General Land office survey set a wood post at this location and bearing trees were recorded.

14" Blk Oak	S 22 W	9 links
8" Blk Oak	S 77 E	68 links

1985 William Lunser, LS 9394, set a cast iron monument at a corner position on line between stones at the West 1/4 corner of Sec. 14 and at the center of Sec. 14, extended east and doubling the distance from the stone at the center and a fence line south at 1340.56 feet east of the center stone. He states position is corroborated by a fence line. He filed a Certificate of Location (#173434). He notes the following distances:

5274.98 feet to the West 1/4 Corner of Sec. 14  
1340.56 feet to a fence line south  
2722.97 feet to the NE Corner of Sec. 14

2002 Found no resurvey information on this corner in the Benton County records.

2002 Westwood Professional Services, Inc.  
County Coordinates obtained by GPS (CIM)  
NAD 83 (1996 Adjustment)  
N-150787.141  
E-473418.822

2004 MN/DOT  
County Coordinates obtained by GPS  
NAD 83 (1996 Adjustment)  
N-150787.233  
E-473418.803

2002 Westwood Professional Services, Inc. found a cast iron monument agreeing with 1985 Lunser ties and distances. Position appears to agree with longstanding occupation of field lines and is accepted as marking the obliterated position for this corner. Coordinates obtained by GPS coincide with 2002 position.