

Statement of Evidence:

F273

East Quarter Corner of Section 27, Township 37 North, Range 31 West, Watab Township, 4th Principal Meridian, Benton County, Minnesota.

1850 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.
20" Bur Oak N 78 1/4 E 79 links
12" Bur Oak N 79 1/2 W 326 links

1946 MN/DOT alignment map for TH 10 shows corner assumed on fence line east.

1980 William Lunser, LS 9394, set a 1/2" iron pipe at a proportionate measurement between the SE and NE Corners of Section 27. He filed a Certificate of Location (#158868) and notes a distance of 2651.53 feet to both the NE and the SE Corners of Section 27.

2003 Westwood Professional Services, Inc. found a MN/DOT cast iron monument. Measured 2662.62 feet to the NE corner and 2662.58 feet to the SE corner of Section 27. Corner found fits the lost position.
County Coordinates obtained by GPS
NAD 83 (1996 Adjustment)
N-140132.058
E-467997.572

2008 Westwood Professional Services, Inc. found a MN/DOT cast iron monument. Measured 2662.62 feet to the NE corner and 2662.58 feet to the SE corner of Section 27. Corner found fits the lost position. CIM is accepted as marking the obliterated position for this corner. Coordinates obtained by GPS coincide with 2003 position.