

**Statement of Evidence:**

**F353**

East Quarter Corner of Section 35, Township 37 North, Range 31 West, Watab Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1850 Original US General Land Office surveyor, John Ryan, set a wood post at this location and bearing trees were recorded.

6" Blk. Oak	N 84 1/2 W	65 links
6" Blk. Oak	N 70 1/2 E	223 links

1982 David Regan, LS 12236, found a RR spike in the centerline of a township road north, County Road 57 east/west and County Road 69 west. He set cast iron monument at the location and filed a Certificate of Location (#163366).

1999 Survey information from MN/DOT gives the following coordinates:  
NAD83 (1986 ADJ.)  
N – 134790.718  
E – 473207.036

2000 Westwood Professional Services, Inc. found a 1/2" iron pin at the corner location.

2002 MN/DOT Right of Way Plat 5-19 shows iron pin over a cast iron monument.

2003 Westwood Professional Services, Inc. obtained coordinates to a PK nail.  
County Coordinates Obtained by GPS  
NAD 83 (1996 Adjustment) – **DO NOT USE WITHOUT CHECKING**  
N- 134791.128  
E – 473206.593

2004 Found 1/2 " iron pin and measured 2666.54 feet to the NE corner and 2670.59 feet to the SE corner.  
County Coordinates obtained by GPS to pin.  
NAD 83 (1996 Adjustment)  
N-134791.034  
E-473206.526

2008 Westwood Professional Services, Inc. found a 1/2" iron pin at the corner location fitting two of Regan's 1982 ties. Position fits occupation of roads and ~2.3 feet of a lost position. 1/2" iron pin is accepted as marking the obliterated position for this corner. Coordinates obtained by GPS coincide with 2004 position.