

Statement of Evidence:

F363

East Quarter Corner of Section 36, Township 37 North, Range 31 West, Watab Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.
10" Blk. Oak N 65 1/2 E 618 links

1938 County Engineers' Notebook No. 116 shows survey of SAR 1 running from south to north. Notes show corner being a spike in center of north-south road and road west. Ties:
FP NW 39.9'
15" Oak NE 67.4'
Stationing gives distances of 2654.8 feet to the SE corner and 2650.7 feet to the NE corner with a delta angle of 0-39' right.

1990 Paul Wollen, LS 10461, found a 3/4" pipe at the intersection of County Road 1 (running north and south) and County Road 57 (from the west). He set a cast iron monument over it and filed a Certificate of Location (#202365).

2004 Westwood Professional Services, Inc. found a CIM and measured 2655.30 feet to the NE corner and 2659.51 feet to the NE corner.
County Coordinates obtained by GPS to CIM.
NAD 83 (1996 Adjustment)
N-134807.223
E-478536.502

2008 Westwood Professional Services, Inc. found a CIM at the corner location. Only one tie from Wollen Certificate of location remains, and CIM fits this tie.
Measured 2659.51 feet to the SE corner and 2655.30 feet to the NE corner which is consistently long (4.71 feet long to SE and 4.61 feet long to NE). CIM is accepted as marking the obliterated position for this corner. County Coordinates obtained by GPS coincide with 2004 position.