

Statement of Evidence:

F06A

Meander Corner No. 1 on the North Line of Section 6, Township 37 North, Range 31 West, Watab Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.
12" Bur Oak S 27 E 109 links
8" White Ash S 70 E 421 links
Line tree 18" Bur Oak East 5.66 chains
This corner is 34.78 chains west of the NE Corner of Section 6.

1986 On September 29, 1986 Paul Wellen, LS 10461, set a cast iron monument for a witness to the north line of Section 6 and filed a Certificate of Location (#182956).

1995 Comstock and Davis performed GPS work under contract with Benton County and Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to a CIM:
N- 164280.534
E – 449838.107

2010 Westwood Professional Services, Inc. found a CIM 2,223.04 feet west of the NE corner of Section 6 at the location reported by Paul Wellen in 1986 and Comstock Davis in 1995. The position of the Meander Corner is 34.78 chains (2,295.48 feet) west of the NE corner of Section 6 and falls in the Mississippi River. The CIM was accepted as a witness corner on the north line of Section 6 and reference ties were established.

County Coordinates – Witness Corner
NAD 83 (1996 Adjustment)
N-164280.87
E-449837.39

County Coordinates – Meander Corner No. 1 (in river)
NAD 83 (1996 Adjustment)
N-164282.22
E-449764.98