

Statement of Evidence:

F06B

Witness Corner to Meander Corner No. 2 on the East Line of Section 6, Township 37 North, Range 31 West, Watab Township, 4th Principal Meridian, Benton County, Minnesota.

1850 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

5" Blk Oak	N 34 1/2 W	38 links
5" Blk Oak	S 89 E	16 links

This corner is 21.50 chains south of the NE Corner of Sec 6.

1986 Paul Wollen, LS 10461, set a cast iron monument on what he established as the east line of Section 6 for a witness corner. No information is given on how point was determined or distance from the NE corner. He filed Certificate of Location (Doc. No. 182957).

2002 No resurvey information has been found on this corner in the Benton County records.

2008 Westwood Professional Services, Inc. found a CIM at this corner location. GLO notes show the location of the meander corner 1419 feet south of the NE corner of Section 6 which would put the corner in the river. The CIM measures 1358.79 feet south of the NE corner (60.21 feet north of the MC) The CIM falls ~15 feet east of the southerly extension of the east line of the SE1/4 of Section 31 to the north, and ~5 feet west of a line drawn cardinal direction South from the NE corner of Section 6. CIM does fit a longstanding fence line and occupation along the east line of Section 6. CIM is accepted as marking the obliterated position for this corner. County coordinates obtained by GPS (Cast Iron Monument)
NAD 83 (1996 Adjustment)
N - 162880.650
E - 452055.094