

Statement of Evidence:

F091

North Quarter Corner of Section 9, Township 37 North, Range 31 West, Watab Township, 4th Principal Meridian, Benton County, Minnesota.

1850 Original US General Land Office survey set a wood post in a mound with a pit 8 links west for the corner location.

This corner is noted on the following recorded plats:

SENTINEL BIGHT 8/7/1979 William Lunser

1972 Survey by H.G. Elletson, LS 728, of a 3-acre parcel in the SE ¼ of Section 4 shows an IM at the corner.

1978 Survey notes of Paul Wellen, LS 10461, show iron pipe at corner with a distance of 2662.09 feet to the NE corner of Section 9.

1982 David Regan, LS 12236, found a 1/2" pinched iron pipe in the centerline of a road running east and west and the centerline of a tangent to a County Road to the south. He set a cast iron monument over the iron and filed a Certificate of Location (#163361).

No Date County Highway ties are the same as Regan's to a ¾ " iron pipe.

2002 Westwood Professional Services, Inc. found a CIM per Regan's certificate.
County Coordinates Obtained by GPS to CIM
NAD 83 (1996 Adjustment)
N-158794.951
E-460191.256

2004 MN/DOT
County Coordinates obtained by GPS
NAD 83 (1996 Adjustment)
N-158795.013
E-460191.228