

Statement of Evidence:

F341

North Quarter Corner of Section 34, Township 37 North, Range 31 West, Watab Township, 4th Principal Meridian, Benton County, Minnesota.

1850 Original US General Land Office surveyor, John Ryan, set a wood post at this location and bearing trees were recorded.

12" Blk Oak	S 61 1/2 E	18 links
10" Blk Oak	N 8 E	98 links

This corner is noted on the following recorded plats

<i>MNDOT ROW PLAT 5-19</i>	4/26/2002	Granite Stone
<i>MNDOT ROW PLAT 5-17</i>	4/26/2002	Pointed Stone

1946 MN/DOT Information;

Roll E-3 (File No. 34-23) and Roll D-8 (File No. 33-9) of MN/DOT alignment maps, show the corner, a pointed stone, is at the intersection of fence lines south and west. They also note distances of 2313.4 feet east to the centerline and a distance of 2668.0 feet to the NE Cor Sec 34.

1980 William Lunser, LS 9394, found a 1 1/2" pipe 1.5 feet east of a pointed stone on a fence line west/south. He filed a Certificate of Location (#158869). Shows a distance of 2664.51 feet to the NE corner of Sec. 34.

1999 James Kramer, LS 23668, surveyor with MN/DOT, found a pointed granite stone (1.0' X 1.4') sticking 1.5 feet above the ground. He filed a Certificate of Location (#265886). Shows a distance of 2667.03 feet to the NE corner of Sec. 34.

Survey information from MN/DOT gives following coordinates:

N – 137448.877
E – 465285.798

2003 Westwood Professional Services, Inc. obtained GPS coordinates on pointed stone. Measured 2666.59 feet to the NE corner of Section 34.

County Coordinates Obtained by GPS

NAD 83 (1996 Adjustment)

N-137449.282

E-465285.698